

Méthodes Python de pilotage de GMSH

Résumé :

Ce document présente le superviseur permettant de piloter GMSH depuis Python, et donc depuis le fichier de commandes Aster.

Ce superviseur produit tout type de maillages 2D en utilisant le logiciel GMSH (www.geuz.org/gmsh). Il est notamment utilisé dans Aster par l'outil de post-traitement interactif STANLEY afin de générer des éléments de maillage pour le post-traitement, mais peut être étendu à d'autres applications : maillage paramétrique, remaillage, etc.

1 Mode d'emploi

Il y a quatre étapes à suivre pour produire un maillage avec le superviseur GMSH :

- 1) Définition de la géométrie ;
- 2) Définition des discrétisations ;
- 3) Création du maillage GMSH et des `GROUP_MA` et objets « Physical » associés ;
- 4) Importation du maillage GMSH dans Aster.

Exemple simple d'utilisation :

Dans l'exemple suivant, on utilise les fonctionnalités du superviseur pour générer le maillage d'une plaque rectangulaire :

Géométrie

```
from Utilitai.sup_gmsh import *

larg = 5.
H_beton = 3.
H_S1 = 4.
t_beton = 25.
prog_S1 = 1.1
```

On importe le module et on définit quelques paramètres.

```
# Geometrie
O = Point(0, 0)
A = Point(larg, 0)
B = Point(larg, H_beton)
C = Point(0, H_beton)
D = Point(0, -H_S1)
E = Point(larg, -H_S1)

OA = Line(O,A)
AB = Line(A,B)
BC = Line(B,C)
OC = Line(O,C)

OD = Line(O,D)
DE = Line(D,E)
AE = Line(A,E)

S2 = Surface(OA,AB,BC,OC)
S1 = Surface(OD,DE,AE,OA)
```

On crée des points, des lignes entre les points et des surfaces à partir des lignes.

```
# Discretisation
OA.Transfinite(1)
BC.Transfinite(1)
DE.Transfinite(1)

N_beton = int(H_beton/t_beton + 0.5)
AB.Transfinite(N_beton)
OC.Transfinite(N_beton)

N_S1 = Progress(H_S1, r=prog_S1, h=t_beton)
OD.Transfinite(N_S1,prog_S1)
AE.Transfinite(N_S1,prog_S1)

S2.Transfinite()
S1.Transfinite()
```

On définit la discrétisation des lignes et des surfaces.

```
# Maillage
mesh = Mesh()
mesh.Physical('FOND',DE)
mesh.Physical('LAT_G',OC,OD)
mesh.Physical('LAT_D',AB,AE)
mesh.Physical('INTERFAC',OA)
mesh.Physical('HAUT',BC)
mesh.Physical('S2',S2)
mesh.Physical('S1',S1)
```

On crée l'objet maillage et on définit les groupes de mailles qui seront des `GROUP_MA` dans la SD maillage Aster et des « *Physical* » dans GMSH (ces derniers seront nommés *GM1*, *GM2*, etc...).

```
MA = mesh.LIRE_GMSH(
    MODI_QUAD = 'OUI'
)
```

Importation du maillage dans Aster : *MA* est un maillage Aster.

2 Liste des fonctions disponibles

La liste des fonctions est extraite directement du source, `sup_gmsh.py`, ce qui explique qu'elle soit en anglais.

2.1 Classe générique pour les objets géométriques

```
class Geometric :

    private attribute
    parameters      : dictionnary of the attributes (except relation and
parameters itself)
                      see __getattr__ and __setattr__

    Attributes
    num              : index among gmsh objects
    md               : mesh descriptor
    mesh             : related mesh object
    relation          : model object in case of coincidence

    Public methods
    Is_point         : return true is the object inherits of the Point class

    Is_line          : return true is the object inherits of the Line class

    Is_surface       : return true is the object inherits of the Surface class

    Is_volume        : return true is the object inherits of the Volume class

    Is_same_dimension : return true is both objects are of the same
dimension
                      (point, line, surface or volume)
    in -> object to compare to self

    Duplicate        : duplicate an object and base its mesh_descriptor
                      on the mesh_descriptor of the model

    Coincide         : assert that an object is coincident with a model one
                      All the attributes are then automatically read from
                      the model object (see __setattr__ and __getattr__).
    in -> model object

    Private method

    Root :
    Provides the root object of an object, ie the object itself if there
is no relation
    or the deepest model in case of relation.

    Geometric_coincide : check if a geometrical coincidence is possible
                      return information about the coincidence, false
else.
    in -> model object
```

Deep_coincide : proceed recursively to ensure coincidence of the relevant sub-objects
in -> model object
in -> correspond (information returned by Geometric_coincide)

__setattr__ : distinguish two sets of attributes
relation (to express a relation with a model object in case of coincidence)
all the other attributes which are stored in the dictionary parameters
instead of the usual __dict__ if there is no relation (see Coincide)
and in the model object if there is a coincidence

__getattr__ : if the object is related (relation <> None) the attribute is read
in the model object. Else, it is read in the current object, actually
in the dictionary parameters (see __setattr__)

Thanks to these two overloaded methods, the access to the attributes is usual if
there is no relation whereas the attributes of the model object are accessed transparently if there is a relation .

__cmp__ :
The comparison of two objects involves possible coincidence. It is no more the object ids
that are compared but the object roots (.relation if any).

Gmsh : produce the source code for Gmsh
in -> mesh

Gmsh_send : send a line code to the gmsh interpreter
in -> line_code (string)

Intermediate_meshing : produce the source code for the intermediate objects
in -> mesh

Object meshing : produce the source code for the current object
var -> object number (modified if several objects are created)

2.2 Fonctions pour les objets POINT

class Point(Geometric) :

Public methods

__init__ :
in -> coordinates (the 3rd is zero by default)

Size : set the size of the neighbouring elements
in -> size

Attractor : define the point as an attractor
in -> scale_x : size amplification factor in the x-direction
in -> scale_y : size amplification factor in the y-direction
in -> distance: influence distance for the perturbation

Attributes

coor : coordinates
size : neighbouring element size
attractor : parameters of the attractor

2.3 Fonctions pour les objets LIGNE

```
class Line(Geometric) :  
  
    LINE OBJECT  
  
    Public methods  
  
    Attractor : define the point as an attractor  
        in -> scale_x : size amplification factor in the x-direction  
        in -> scale_y : size amplification factor in the y-direction  
        in -> distance: influence distance for the perturbation  
  
class Circle(Line) :  
  
    CIRCLE OBJECT  
  
def Curve(l_x,l_y,l_z=None) :  
  
    CURVE OBJECT (in -> list of points)
```

2.4 Fonctions pour les objets SURFACE

```
class Surface(Geometric) :  
  
    SURFACE OBJECT (inherit from the Geometric class)  
  
    Public methods  
        __init__ :  
            in -> lines : external bounday of the surface (lines should be  
connected)  
  
        Holes : set the internal holes (surfaces)  
            in -> holes : list of holes  
  
        Boundary : checks that the boundary is a closed loop and returns the  
orientation of the edges  
  
        Ruled : declare the surface is a ruled one  
  
        Translate : translate the surface  
            in -> tran : (numpy) vector of translation  
  
        Recombine : recombine the surface (try to mesh with quadrangles instead  
of triangles)  
  
        Transfinite : Declare the mesh to be transfinite  
  
    Attributes  
        lines : list of external boundary lines  
        holes : list of internal holes (surfaces)  
        ruled : indicates (false or true) if the surface is a ruled surface
```

```
loops : list of boundary (external and internal) loops (computed when  
meshing)
```

2.5 Fonctions pour les opérations sur les maillages

class Mesh_Descriptor :

```
Attributes
    relation      Another mesh descriptor provides the mesh parameters
    parameters    dictionary of the mesh parameters
                    size      Point size
                    transfinite Transfinite mesh (0 or 1)
                    number    Number of elements along a line
(transfinite)
                    progression Progression of element size
(transfinite)
                    recombine   Recombine mesh or not
```

Specific access :

```
md.parameter_name = xxx -> the relation is destroyed (set to None)
xxx = md.parameter_name -> if there is a relation, the effective
                           parameter is looked for recursively
```

Deep copying : a relation is set to the model instead of a true copy

class Mesh :

```
def __init__(self, algo = 2, gmsh='gmsh') :

def Physical(self, name, *l_obj) : creation of Physical (GMSH object)

def Save(self, file = 'fort.geo') : save the geo file

def View(self) : launch GMSH with the current geo file

def Create(self, file = 'fort.19') : save the geo file and create the msh
file

def Name(self, MA, CREA_GROUP_NO ) : create the group_ma and/or the
group_no

def LIRE_GMSH (self,
    UNITE_GMSH      = 19,
    UNITE_MAILLAGE  = 20,
    MODI_QUAD       = 'NON' ,
    CREA_GROUP_NO   = 'OUI'
) :
```

Lecture du maillage (format Aster) à partir de sa définition (format sup_gmsh)

```
UNITE_GMSH      = Numéro d'unité logique pour le fichier msh
UNITE_MAILLAGE  = Numéro d'unité logique pour le fichier mail
MODI_QUAD       = 'OUI' si line->quad, 'NON' sinon
CREA_GROUP_NO   = 'OUI' si on crée les GROUP_NO, 'NON' sinon
```

2.6 Fonctions pour les transformations géométriques

```
def VectorProduct(u,v) :
```

```
def VectorNorm(u) :
```

```
class Rotation :
```

in -> A,C,B